# CARIZZMA VOC-compliant special effect system: Granite Effect



Please also see the technical data sheet "CARIZZMA Substrates and Pretreatment"

### General information:

For this special effect system you need a covering basecoat. In the second step you apply the special effect coat by sprinkling the basecoat first with black, then with grey and finally with white ONYX HD paint. As a last step you apply the finishing clear. The special effect is achieved by using a suitable colour combination. You should use shades of black, white and grey.

## 1. Basecoat:

Mixing ratio:	ONYX HD grey HYDROMIX	100% by vol. 60% by vol.
Spraygun and pressure: Number of spraycoats: Flash-off:	1.5 mm HVLP / 2.0 bar 2 until mat after each spraycoat.	

## 2. Special effect coat:

	Mixing ratio:	ONYX HD black or white HYDROMIX	100% by vol. 60% by vol.
	Spraygun and pressure: Technique: Flash-off:	1.5 mm HVLP / less than 0.5 bar Sprinkling until mat after each spraycoat.	

Note: You can sprinkle on grey paint between the black and white paints.

### 3. Finishing clear:



Mixing ratio:	CARIZZMA CUSTOMCLEAR CP H 420 SC 850	300% by vol. 100% by vol. 100% by vol.
Spraygun and pressure: Number of spraycoats: Flash-off: Drying:	1.3 – 1.5 mm HVLP / 2.0 bar 2 3 min. between spraycoats 30 min. at 60°C	

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

R-M Automotive Refinish Paints, Z.I.du Merret F-60676 Clermont de l'Oise Cedex, Tel. (33) (0) 3 44 77 77 77, 11/2012