

AIR Tune-R

A 2P15

eSense air drying additive



Application:	This product is used in PIONEER Series clear coat materials.
Key Features:	Using A 2P15 AIR Tune-R will allow for a dust-free surface more quickly. Sandability, polishability and readiness for assembly will be significantly improved.
Remarks:	Use additive A 2P15 AIR Tune-R at room temperature > 20°C only. Ambient temperature and film build can greatly affect the drying behavior. Mixing ratio / Application: As specified in the technical data sheet of the product in which A 2P15 AIR Tune-R is being used.

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.



Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

