

# PLASTIC Prim-R

## PM 2P10 Primer

<b>Application:</b>	Pioneer Series - undercoat solutions.
<b>Key Features:</b>	Eco effectiveness aerosol can - high performance on plastic parts.
<b>Remarks:</b>	The material is ready for use. <b>Product is suitable on</b> Pur-RIM / PP-EPDM / ABS / GRP-SMC / PC-PBTP / PA / PPO / rigid PVC

---

<b>Storage temperature</b>	5-45 °C
<b>Shelf life</b>	24 months

---



### Cleaning

Clean with PK 1P10 or PK 2P10 using a sanding pad. Clean with PK 2P10.

---

### Handling



Do not use deformed aerosol cans. While shaking the can, do not strike against solid objects. During shaking, the mixing balls are released. Avoid bumps, friction and impact.



Shake vigorously for 2 min before each use.



Number of spray coats: 1-2  
Film thickness: 5-10 µm  
Flash off at 20°C: approx. 15 min

---

### Safety advice:

**2004/42/IIIB(e)(840)688:** The EU limit value for this product (product category: IIB.e) in ready-for-use form is max 840 grams of VOC per liter. The VOC content of this product is 688 g/l.

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at [www.rmpaint.com](http://www.rmpaint.com) or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

# PLASTIC Prim-R

## PM 2P10 Primer

### Drying



Drying at 20°C      15 min

### Remark

Apply PIONEER Series filler SANDING FILL-R+ White / Grey / Black, AIR Purpos-R White / Grey / Black or UV FILL-R Light Grey / Grey / Dark Grey wet on wet.  
Apply PLASTIC Prim-R again when the flash off time exceeds 30 min at 20°C.

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

### Safety advice:

**2004/42/IIIB(e)(840)688:** The EU limit value for this product (product category: IIB.e) in ready-for-use form is max 840 grams of VOC per liter. The VOC content of this product is 688 g/l.

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at [www.rmpaint.com](http://www.rmpaint.com) or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

