

AGILIS

R-M AGILIS Variant Factory Pack

Application: Mixture of AGILIS mixed tinters with mixing clear HB 010 / HB 030.
Please observe the mixing ratio on the label.
Mixture will keep for six months when stored in closed plastic containers or cans coated inside.



Paint System

Please refer to the INFO R-M module "R-M AGILIS" for further details and information about application processes.

2:1



Mixing Ratio

100 % by volume

R-M AGILIS Factory pack



Thinner

50 % by volume

RA 050 Thinner
(acc. to mixing formula)
Stir IMMEDIATELY after adding.

Safety advice:

2004/42/IIIB(d)(420)249: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 249 g/litres.

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



AGILIS

R-M AGILIS Variant Factory Pack



HVLP spray gun



Compliant gravity-feed spray gun

Application pressure	2 bar
Nozzle size	1.3-1.4 mm
Number of spray coats	1 full coat + 1 "Finish coat" applied wet-on-wet.
Flash off at 20°C	Flash off until the surface is completely mat after the "Finish coat".
Film thickness	10-15 µm
Application Remark	Spraying pressure = Inlet pressure The setup depends on the spray gun supplier, please refer to the INFO R-M module "BASIC KNOWLEDGE - BODYSHOP EQUIPMENT" for detailed information

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

2004/42/IIIB(d)(420)249: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 249 g/litres.

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

