

BLENDING FLASH

A 2540

Additive for small repairs

Application: Smoothes transition areas by use of blending processes.

Remarks: The product is ready for use. Shake well before use

Density 0.86-0.96 g/cm³

Storage temperature 5-45 °C

Shelf life 24 months



Spray viscosity at 20°C DIN 4: 13 s **Potlife at 20°C**
ISO 4: 17 s



HVL spray gun



Compliant gravity-feed spray gun

Nozzle size 1-1.2 1-1.2

Number of spray coats 2 – 3 spraycoats to the clear fade-out areas to smooth them.

Application Remark Mini spray gun
0.5 – 0.7 bar at the nozzle

Drying

Drying Remark As recommended for the R-M clear used.

Safety advice:

2004/42/IIIB(e)(840)839: The EU limit value for this product (product category: IIB.e) in ready-for-use form is max 840 grams of VOC per liter. The VOC content of this product is 839 g/l.

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



BLENDING FLASH

A 2540

Additive for small repairs

Remark

If necessary, minor defects can be polished out with any standard fine polishing compound once the clear coat has fully cured.

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

2004/42/IIIB(e)(840)839: The EU limit value for this product (product category: IIB.e) in ready-for-use form is max 840 grams of VOC per liter. The VOC content of this product is 839 g/l.

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

