

STOP MULTI

B 2442

Multi-purpose putty, white Variant for CV

Application:	all applications
Key Features:	<ul style="list-style-type: none">• fast drying• suitable on all substrates• good filling properties• fast sandable
Remarks:	The substrate should be clean, free of dust, rust, oil and grease.



Paint System

Solid Content (RFU ~96%)

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/IIIB (b)(250)180: The EU limit value for this product (product category: IIB(d)) in ready to use form is max. 250 g/l. The VOC content of this product is 180 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



STOP MULTI

B 2442

Multi-purpose putty, white Variant for CV

Handling

Substrates:

Very well suited:

- Steel
- Galvanized Steel
- Aluminium

Well suited:

- GRP/SMC
- R-M CV Primer-Filler / Filler
- Powder coating
- Coil-coating
- Plywood
- Wood
- OEM-Paintwork
- Old paint work



Suited in some cases:

- Stainless steel

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/IIIB (b)(250)180: The EU limit value for this product (product category: IIB(d) in ready to use form is max. 250 g/l. The VOC content of this product is 180 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



STOP MULTI

B 2442

Multi-purpose putty, white Variant for CV

100:2 - 3 by weight



Mixing Ratio

B 2442 Multi-purpose putty



Hardener

D 2465 Hardener



Spray viscosity at 20°C

DIN 4:

Potlife at 20°C

4 min

Drying



Drying at 20°C

Sandable:
20 - 30 min.

Remark

Can be sanded after 20-30 min
Not suitable for applications that require elasticity, e.g. weld seams.
Do not apply on etch wash primer or acid pre treated substrates!

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/IIIB (b)(250)180: The EU limit value for this product (product category: IIB(d) in ready to use form is max. 250 g/l. The VOC content of this product is 180 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.