

GHD TRANSPARENT SEALER CP

P 2425

Variant for CV

Application: sign writing, cabs (color change), multi - color painting, GHD TOPCOAT line, powder coated profiles / boxes

Key Features:

- tintable
- brilliant top coat appearance
- fast drying

Remarks: The substrate should be clean, free of dust, rust, oil and grease.



Paint System Solid Content ~66% (RFU ~53%)

Spreading rate 406 m²/l at 1 µm

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/II B (c II)(540)502: The EU limit value for this product (product category: IIB(d) in ready to use form is max. 540 g/l. The VOC content of this product is 502 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



GHD TRANSPARENT SEALER CP

P 2425

Variant for CV

Handling

Substrates:

Very well suited:

- R-M CV Primer
- R-M CV Primer-Filler / Filler
- Powder coating
- Coil-coating
- Wood
- OEM-Paint work
- Old paint work



Suited in some cases:

- GRP / SMC
- Plywood



Suction cup:

Application pressure 2.5 bar

Nozzle size 1.7

Number of spray coats 1

Film thickness 20 - 25 µm

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/IIIB (c II)(540)502: The EU limit value for this product (product category: IIB(d) in ready to use form is max. 540 g/l. The VOC content of this product is 502 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



GHD TRANSPARENT SEALER CP

P 2425

Variant for CV

100:50 + 30% by volume



Mixing Ratio

P 2425 Transparent acrylic 2K sealer



Hardener

H 360 Hardener for GHD undercoat materials, normal



Thinner

GV 100 Thinner, fast
GV 200 Thinner, medium
GV 300 Thinner, slow





Spray viscosity at 20°C

DIN 4: 17 s

Potlife at 20°C

3 h

		 HVLP spray gun	 Compliant gravity-feed spray gun
Application pressure	bar	2	2.2-2.5
Nozzle size		1.5	1.4
Number of spray coats			1
Film thickness	µm		20-25

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/IIIB (c II)(540)502: The EU limit value for this product (product category: IIB(d) in ready to use form is max. 540 g/l. The VOC content of this product is 502 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



GHD TRANSPARENT SEALER CP

P 2425

Variant for CV

Drying



Drying at 20°C

Overcoatable:

Min: 15 min.

Max: 2 h

Remark

TRANSPARENT SEALER CP can be tinted with (up to 10% of) GHD TOPCOAT Line Topcoat.

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/II B (c II)(540)502: The EU limit value for this product (product category: IIB(d) in ready to use form is max. 540 g/l. The VOC content of this product is 502 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

