

GRAPHITE HD CV PRIMER TINTING PASTE, black

Resin base Modified urea resin Mixing ratio max. 10% by Vol. in Undercoats → GHD Chassis Surfacer, GHD Primer Filler MP, GHD Surfacer, GHD Epoxy und Epoxy CF Hardener See according data sheet Reducer See according data sheet VOC level: - RFU in mentioned GRAPHITE **Spray viscosity** HD Undercoats < 540 g/l Potlife Number of **Spraying** Material Nozzle Compliant Application spraycoats pressure pressure diameter gun Double membrane pump Pressure pot Airless/Airmix Gravity-feed spraygun Suction-feed spraygun Dry film thickness See according data sheet Spreading rate (DIN 53 219) Solids content ~ 56 % weight (DIN EN ISO 3251)

Flash-off at 20°C



Drying Recoatable Tabeable

Panel temperature 20°C

60°C

Substrates See according data sheet of the primer

Remarks Processing data of the mentioned primer and primer fillers do not change by

adding Graphite HD CV Tinting Primer Paste



Please refer to the EU Material Safety Data Sheet for product labelling as required by Directive 1999/45/EC and the respective national rules. The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. It cannot be ruled out that this product contains particles < 0.1 µm.

R-M Automotive Paint F-60676 Clermont de l'Oise Cedex

Tel. (33) (0) 3 44 77 77 77

www.rmpaint.com

Feb. 2010