













STOP MULTI

Product code: SP66-128F

Resin base	Unsaturated polyester				
 Mixing ratio	100 : 3 by weight				
 Hardener	PUTTY HARDENER				
 Reducer					
 Spray viscosity	4 min.				
 Potlife					
 Application	Number of spraycoats	Spraying pressure	Material pressure	Nozzle diameter	Compliant gun
Double membrane pump Pressure pot					
 Gravity-feed spraygun					
 Suction-feed spraygun					
Dry film thickness					
Spreading rate (DIN 53 219)	- m ² /l at 1 µm film thickness				
Solids content (DIN EN ISO 3251)	Above 98% by weight ± 2				
 Flash-off at	20°C				
 Drying	Recoatable	Tack-free	Tapeable	Ready for assembly	
Panel temperature	20°C				
	60°C				
Substrates	Steel, aluminium, galvanised steel				
Remarks	Can be sanded after 20 min. Not suitable for applications that require elasticity, e.g., weld seams.				
2004/42/IIB(b) (250)180	The EU limit value for this product (product category: IIB.b) in ready to use form is max 250 g/litre of VOC. The VOC content of this product is 180 g/litres.				

Please refer to the EU Material Safety Data Sheet for product labelling as required by Directive 1999/45/EC and the respective national rules. The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. It cannot be ruled out that this product contains particles < 0.1 µm.

R-M Automotive Paint
F-60676 Clermont de l'Oise
Cedex

Tel. (33) (0) 3 44 77 77 77

www.rmpaint.com

Feb. 2010

