ONYX EASY BLENDER

A 2520

Additive for blending repairs

Application: Water-based additive for refinishing with ONYX HD using a BLEND'ART process.

For use in BLEND'ART processes either as a transparent pre coat or as an additive in

ONYX HD.

Remarks: • Shake well before use.

Storage temperature 5-45 °C
Shelf life 12 months



Cleaning

See process described in BLEND'ART ONYX HD.

Mixing Ratio 100 Parts by vol

A 2520 Additive for blending repairs



Thinner

60 Parts by vol

HB 032 HYDROMIX HB 034 HYDROMIX slow

Potlife at 20°C 7 days

Safety advice:

2004/42/IIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready-for-use form is max 420 grams of VOC per liter. The VOC content of this product is 419 g/l.

It cannot be ruled out that this product contains particles < 0.1 μm .

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment. The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

page 1 of 2 05/2023

Perfection made simple



ONYX EASY BLENDER

A 2520

Additive for blending repairs

	HVLP spray gun	Compliant gravity-feed spray gun
Nozzle pressure	0.7 bar	
Nozzle size	1.4-1.5	
Number of spray coats	See process described in BLEND'ART ONYX HD.	
Application Remark	Minijet HVLP 1.0 mm 0.7 bar at the nozzle. Select spraygun according to size of area to be refinished.	
Drying		
Drying Remark	See process described in BLEND'ART ONYX HD.	

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

2004/42/IIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready-for-use form is max 420 grams of VOC per liter. The VOC content of this product is 419 g/l.

It cannot be ruled out that this product contains particles $< 0.1 \, \mu m$.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment. The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

page 2 of 2 05/2023

Perfection made simple

