

PK 900

PK 900 Cleaning agent

Application: Cleaner, for use on surfaces which will be refinished.
PK 900 is particularly suitable for cleaning bare metal surfaces as well as OEM finishes which will be repaired using TRANSPARENT SEALER CP.

Remarks: Do not use the cleaner on solvent-sensitive or thermoplastic substrates.

Density	0.73-0.83 g/cm ³
Storage temperature	5-45 °C
Shelf life	36 months



Cleaning

Soak a clean and dry lint-free cloth with PK 900. Clean small areas of approx. 0.5 m² of the surface to be painted and wipe these areas immediately afterwards with a dry cloth of the same quality. PK 900 should not dry on the surface being treated. Attention: Individual paint coats may suffer surface etching from the use of PK 900. In this case, ensure a good flash-off of the substrate before going on with the repair so that no solvents will be trapped in the new paint system. In extreme cases, remove the affected paint coats before applying the new paint system.

PK 900 is ready for use.

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

PK 900: 2004/42/IIB(a)(850)840: The EU limit value for this product (product category: IIB.a) in ready-for-use form is max 850 grams of VOC per liter. The VOC content of this product is 840 g/l.

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of these products please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.