

SPEEDFLASH S

eSense



A 2120E

Accelerator thinner

Key Features:

SPEEDFLASH eSense A 2120E increases the chemical reactivity of the products in which it is used, allowing shorter waiting times before sanding, polishing operations or reassembly can be started. SPEEDFLASH eSense A 2120E is particularly suited for body shops that, in order to save energy, bake the applied clear at panel temperatures below 60°C. SPEEDFLASH eSense A 2120E is particularly suitable for small repairs.

Remarks:

The amount of SPEEDFLASH eSense A 2120E to be added corresponds with the amount of thinner indicated in the standard mixing ratio.

Solid Content	1 %
Density	0.82-0.92 g/cm ³
Storage temperature	5-45 °C
Shelf life	36 months



Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product, please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions.

You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

