

Additive to accelerate drying

Product Category: **C 5**

### Fields of use

Additive to accelerate drying of RAPIDCLEAR C2570E eSense on vertical surfaces

### Additional Information

SPEEDFLASH S A2120E eSense increases the chemical reactivity of the products in which it is used, allowing shorter waiting times before sanding, polishing operations or reassembly can be started. SPEEDFLASH S A2120E eSense is particularly suited for body shops that, in order to save energy, bake the applied clear at panel temperatures below 60°C. SPEEDFLASH S A2120E eSense is particularly suitable for small repairs.

### Technical characteristics

Solids content ~ 1.0 %	Density 0.820–0.920 g/cm <sup>3</sup>
Storage temperature min. 5°C to max. 45°C	Shelf life 36 months

### Application


The amount of SPEEDFLASH S A2120E eSense to be added corresponds with the amount of thinner indicated in the standard mixing ratio.

### Substrate / Pre-treatment / Cleaning

As specified in the technical data sheet of the product in which SPEEDFLASH S A2120E eSense is being used.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these statements do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at [www.mpaint.com](http://www.mpaint.com) or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

R-M Automotive Refinish Paints, Z.I. du Merret F-60676 Clermont de l'Oise Cedex, Tel. (+33) (0) 3 44 77 77 77, 12/2017



	<b>RAPIDCLEAR C 2570E eSense</b> <b>H 2550E eSense</b> <b>SPEEDFLASH S A2120E eSense</b> Mix well and strain before application.	300% by vol. 100% by vol. 100% by vol.		
The use of SPEEDFLASH S A2120E eSense will considerably reduce the potlife of the product in which it is used.				
	As specified in the technical data sheet of the product in which SPEEDFLASH S A2120E eSense is being used.			
	As specified in the technical data sheet of the product in which SPEEDFLASH S A2120E eSense is being used.			
	<b>RAPIDCLEAR C 2570E eSense</b>	<b>20°C</b> 3 – 4 h	<b>40°C</b> 30 min.	<b>60°C</b> 10 – 15 min.

### Finishing

### Safety instructions

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product, please adhere to the actual safety recommendations and the personal protective equipment.