

# PLASTIC Tune-R

A 2P40

eSense plastic adhesion additive



<b>Application:</b>	PIONEER Series - eSense plastic adhesion additive for Pioneer Series undercoats materials: <ul style="list-style-type: none"><li>• MULTI Purpos-R White / Black</li><li>• WET Fill-R White / Black</li></ul>
<b>Key Features:</b>	Additive which makes fillers suitable for direct application to all paintable plastic substrates normally used in the automotive industry.
<b>Remarks:</b>	The addition of PLASTIC Tune-R does not produce adhesion to unpaintable pure polypropylene (PP) and polyethylene (PE). Mixing ratio / Application: As specified in the technical data sheet of the product in which PLASTIC Tune-R is being used.  Storage Temperature: 41-113 °F (5-45 °C) Shelf Life: 24 months

---

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

---



## Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Material Safety Data Sheet (MSDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.

