

# PRE Clean-R

PK 2P20

eSense waterborne cleaning agent, base-/topcoat



**Application:** Pioneer Series - eSense undercoat solutions.

**Key Features:** Eco effectiveness waterborne cleaner - top level performance. PRE Clean-R is used before base- and topcoat application.

**Remarks:** Use a pump spray bottle and wipe dry with a cloth.

Storage Temperature: 41-113 °F (5-45 °C)  
Shelf Life: 24 months

## Handling



before basecoat / topcoat / clear coat or waterborne filler application

### Product suitable on



- Fillers
- Old paintwork
- GRP / SMC

VOC ready for use                      24 g/l                      0.2 lb/gal

1:7



### Mixing Ratio

1 parts by volume

PK 2P20 eSense waterborne cleaning agent, base-/topcoat



### Thinner

7 parts by volume

Distilled / Deionized Water

## Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Material Safety Data Sheet (MSDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.



# PRE Clean-R

PK 2P20

eSense waterborne cleaning agent, base-/topcoat



Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.



**Safety advice:**

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Material Safety Data Sheet (MSDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.

